



Franklin Electric

**Encapsulated Submersible Motors
4" Single Phase 50 Hz
Euro Price List
PSC Motors**

**bulk packed
without lead**

**Motor
& Cable
& Single Pack**

PRICE LIST EFFECTIVE 01-MAY-2011 ORDER DATE

* Normally stocked. Call for Availability. Non-stock - call for lead time.

Model Number	DESCRIPTION	Material	Phases	kW	HP	Voltage	Hertz	Thrust (N)	Net Weight (kg)	Remarks	Цена с НДС, Euro	Price Group	standard lead -not included-	STOCK STATUS	MODEL	attached lead 304SS	Цена с НДС, Euro	STOCK STATUS	
4" SUPER STAINLESS - Permanent Split Capacitor																			
254 803 1621	PSC-0,25-220/230-50-W	W	1	0,25	1/3	220/230	50	1500	7,4	PSC	226,09	4"	310 113 001	*	254 803 1621L	1,5m	255,54		
254 805 1621	PSC-0,37-220/230-50-W	W	1	0,37	1/2	220/230	50	1500	8	PSC	228,12	4"	310 113 001	*	254 805 1621L	1,5m	257,58		
254 807 1621	PSC-0,55-220/230-50-W	W	1	0,55	3/4	220/230	50	1500	9,2	PSC	246,35	4"	310 113 001	*	254 807 1621L	1,5m	275,80	*	
254 808 1621	PSC-0,75-220/230-50-W	W	1	0,75	1	220/230	50	3000	10,4	PSC	266,61	4"	310 113 001	*	254 808 1621L	1,5m	296,05	*	
254 809 1621	PSC-1,1-220/230-50-W	W	1	1,1	1.5	220/230	50	3000	11,8	PSC	311,19	4"	310 113 001	*	254 809 1621L	1,5m	340,65	*	
254 810 1621	PSC-1,5-220/230-50-W	W	1	1,5	2	220/230	50	3000	12,9	PSC	386,13	4"	310 113 001	*	254 810 1621L	1,5m	415,59	*	
254 811 2521	PSC-2,2-220/230-50-W	W	1	2,2	3	220/230	50	4000	17,3	PSC	489,43	4"	310 113 001	*	254 811 2521L	2,5m	525,03	*	
254 813 1621	PSC-0,25-230/240-50-W	W	1	0,25	1/3	230/240	50	1500	7,4	PSC	226,09	4"	310 113 001		254 813 1621L	1,5m	255,54		
254 815 1621	PSC-0,37-230/240-50-W	W	1	0,37	1/2	230/240	50	1500	8	PSC	228,12	4"	310 113 001	*	254 815 1621L	1,5m	257,58		
254 817 1621	PSC-0,55-230/240-50-W	W	1	0,55	3/4	230/240	50	1500	9,2	PSC	246,35	4"	310 113 001	*	254 817 1621L	1,5m	275,80		
254 818 1621	PSC-0,75-230/240-50-W	W	1	0,75	1	230/240	50	3000	10,4	PSC	266,61	4"	310 113 001	*	254 818 1621L	1,5m	296,05		
254 819 1621	PSC-1,1-230/240-50-W	W	1	1,1	1.5	230/240	50	3000	11,8	PSC	311,19	4"	310 113 001	*	254 819 1621L	1,5m	340,65		
254 820 1621	PSC-1,5-230/240-50-W	W	1	1,5	2	230/240	50	3000	12,9	PSC	386,13	4"	310 113 001	*	254 820 1621L	1,5m	415,59		
254 821 2521	PSC-2,2-230/240-50-W	W	1	2,2	3	230/240	50	4000	17,3	PSC	489,43	4"	310 113 001	*	254 821 2521L	2,5m	525,03		
										Adder:	10,13	4"							
Leads																			
310 113 001		LEAD4 - 4x1.5; Length = 1.5m standard							0,24			22,53	Acc		YES				
310 113 401		LEAD4 - 4x1.5; Length = 1.5m 304 SS							0,24			27,50	Acc		YES				
Control Box SubStart SC																			
Can be used with both 220/230V and 230/240V PSC motor ranges																			
284 623 3510	SUB-ST-0.25-230-50-PSC			0,25	1/3						56,93	Acc		*					
284 624 3510	SUB-ST-0.37-230-50-PSC			0,37	1/2						59,20	Acc		*					
284 625 3510	SUB-ST-0.55-230-50-PSC			0,55	3/4						61,48	Acc		*					
284 626 3510	SUB-ST-0.75-230-50-PSC			0,75	1						63,76	Acc		*					
284 627 3510	SUB-ST-1.1-230-50-PSC			1,1	1.5						66,03	Acc		*					
284 628 3510	SUB-ST-1.5-230-50-PSC			1,5	2						81,97	Acc		*					
284 629 3510	SUB-ST-2.2-230-50-PSC			2,2	3						88,80	Acc		*					
W = Standard Material Version																			



Franklin Electric

**Encapsulated Submersible Motors
4" Single Phase 2 wire 50 Hz
Euro Price List**

2 wire Motors

**bulk packed
without lead**

**Motor & Cable &
Single Pack**

PRICE LIST EFFECTIVE 01-MAY-2011 ORDER DATE

Motors listed on this page do not include leads

** Normally stocked. Call for Availability. Non-stock - call for lead time.*

Model Number	DESCRIPTION	Material	Phases	kW	HP	Voltage	Hertz	Thrust (N)	Net Weight (kg)	Цена с НДС, Euro	Price Group	standard lead -not included-	STOCK STATUS*	MODEL	attached lead 304SS	Цена с НДС, Euro	STOCK STATUS*	
4" SUPER STAINLESS - 2 WIRE (1 Lead Required)																		
2-Wire motors are split phase designs with integrated starting components																		
and do not use an above ground control box. Starting with a blocked pump creates a vibration to release blockage.																		
244 755 1221	2W-0.37-230-50-W-LA/OV	W	1	1/3	1/2	230	50	1500	7,8	278,12	4"	310 134 001	*	44 755 1221	1,5m	310,11		
244 757 1221	2W-0.55-230-50-W-LA/OV	W	1	0,55	3/4	230	50	1500	8,6	294,99	4"	310 134 001	*	44 757 1221	1,5m	326,98		
244 758 1221	2W-0.75-230-50-W-LA/OV	W	1	0,75	1,0	230	50	3000	10,0	317,46	4"	310 134 001	*	44 758 1221	1,5m	349,44		
244 759 1221	2W-1.1-230-50-W-LA/OV	W	1	1,1	1,5	230	50	3000	12,3	379,27	4"	310 134 001	*	44 759 1221	1,5m	411,26		
Leads																		
310 134 001	LEAD4-2WIRE-3x1.5; Length = 1.5 m standard								0,2	25,07	Acc		*					
310 134 401	LEAD4-2WIRE-3x1.5; Length = 1.5 m 304 SS								0,2	30,03	Acc		*					
310 132 001	LEAD4-2wire with traction relief and 2 plugs; Length = 1.5 m								0,3	37,62	Acc		*					



Franklin Electric

Encapsulated Submersible Motors & Control Boxes

4" Single Phase 3 wire 50 Hz

Euro Price List

3 wire Motors

bulk packed without lead

Motor & Cable & Single Pack

PRICE LIST EFFECTIVE 01-MAY-2011 ORDER DATE

Motors listed on this page do not include leads

* Normally stocked. Call for Availability. Non-stock - call for lead time.

Model Number	DESCRIPTION	Material	Phases	kW	HP	Voltage	Hertz	Thrust (N)	Net Weight (kg)	Remarks	Цена с НДС, Euro	Price Group	standard lead -not included-	STOCK STATUS*	MODEL	attached lead 304SS	Цена с НДС, Euro	STOCK STATUS*	
4" SUPER STAINLESS - 3 Wire Single Phase (Lead and Control Box not included)																			
3-wire motors are high starting torque, capacitor start designs and feature all corrosion resistant construction with above ground controls. Without lightning arrestor.																			
214 753 1621	3W-0,25-220/230-50-W	W	1	0,25	1/3	220	50	1500	7,2		249,16	4"	310 113 001		214 753 1621L	1,5m	278,62		
214 755 1621	3W-0,37-220/230-50-W	W	1	0,37	1/2	220	50	1500	7,8		251,20	4"	310 113 001		214 755 1621L	1,5m	280,65		
214 757 1621	3W-0,55-220/230-50-W	W	1	0,55	3/4	220	50	1500	8,7		269,42	4"	310 113 001		214 757 1621L	1,5m	298,87		
214 758 1621	3W-0,75-220/230-50-W	W	1	0,75	1	220	50	3000	10,0		289,67	4"	310 113 001		214 758 1621L	1,5m	319,12		
224 750 1621	3W-1,1-220/230-50-W	W	1	1,1	1.5	220	50	3000	12,6		334,26	4"	310 113 001		224 750 1621L	1,5m	363,72		
224 751 1621	3W-1,5-220/230-50-W	W	1	1,5	2	220	50	3000	13,0		409,21	4"	310 113 001		224 751 1621L	1,5m	438,65		
224 752 2521	3W-2,2-220/230-50-W	W	1	2,2	3	220	50	4000	16,9		512,55	4"	310 113 001		224 752 2521L	2,5m	548,13		
214 753 1621	3W-0,25-220/230-50-W	W	1	0,25	1/3	230	50	1500	7,2		249,16	4"	310 113 001		214 753 1621L	1,5m	278,62		
214 755 1621	3W-0,37-220/230-50-W	W	1	0,37	1/2	230	50	1500	7,8		251,20	4"	310 113 001	*	214 755 1621L	1,5m	280,65		
214 757 1621	3W-0,55-220/230-50-W	W	1	0,55	3/4	230	50	1500	8,7		269,42	4"	310 113 001	*	214 757 1621L	1,5m	298,87		
214 758 1621	3W-0,75-220/230-50-W	W	1	0,75	1	230	50	3000	10,0		289,67	4"	310 113 001	*	214 758 1621L	1,5m	319,12		
224 750 1621	3W-1,1-220/230-50-W	W	1	1,1	1.5	230	50	3000	12,6		334,26	4"	310 113 001	*	224 750 1621L	1,5m	363,72		
224 751 1621	3W-1,5-220/230-50-W	W	1	1,5	2	230	50	3000	13,0		409,21	4"	310 113 001	*	224 751 1621L	1,5m	438,65		
224 752 2521	3W-2,2-220/230-50-W	W	1	2,2	3	230	50	4000	16,9		512,55	4"	310 113 001	*	224 752 2521L	2,5m	548,13		
Above motors with lightning arrestor										Adder:	10,13	4"							
4" SUPER STAINLESS - 3 WIRE CONTROL BOXES																			
Start capacitors provide torque start-ups while motor matched run capacitors offer smooth, quiet, efficient motor operation.																			
Reset overloads protect motor and pumping equipment from abnormal conditions.																			
										AR = Automatic Reset; MR = Manual Reset									
280 355 4115	CB-0,25/0,37-220,230,240-50			0.25/0.37	0.33/0.5	220-240	50		1,4	AR	69,69	Acc		*					
280 357 4115	CB-0,55-220,230,240-50			0,55	0.75	220-240	50		1,4	AR	73,66	Acc		*					
280 358 4115	CB-0,75-220,230,240-50			0,75	1	220-240	50		1,4	AR	77,61	Acc		*					
282 350 8114	CB-1,1-220,230,240-50			1,1	1.5	220-240	50		2,8	MR	117,40	Acc		*					
282 351 8114	CB-1,5-220,230,240-50			1,5	2	220-240	50		2,8	MR	163,20	Acc		*					
282 352 8114	CB-2,2-220,230,240-50			2,2	3	220-240	50		3	MR	252,74	Acc		*					
Leads																			
310 113 001		LEAD4 - 4x1.5; Length = 1,5m standard								0,3		22,53	Acc		*				
310 113 401		LEAD4 - 4x1.5; Length = 1,5m 304 SS								0,4		27,50	Acc		*				
W = Standard Material Version																			

**Franklin Electric****Encapsulated Submersible Motors****4" 3 Phases 380/415V 50 Hz****Euro Price List****3~ phase Motors****PRICE LIST EFFECTIVE 01-MAY-2011 ORDER DATE**Motors listed on this page do not include leads** Normally stocked. Call for Availability. Non-stock - call for lead time.***bulk
packed****Motor & Cable &
Single Pack**

Model Number	DESCRIPTION	Material	Phases	kW	HP	Voltage	Hertz	Thrust (N)	Net Weight (kg)	Цена с НДС, Euro	Price Group	standard lead -not included-	STOCK STATUS*	MODEL	attached lead	Цена с НДС, Euro	STOCK STATUS*	
4" SUPER STAINLESS - 3 PHASES (1 Lead Required)																		
234 761 1621	3P-0,37-380/415-50-W	W	3	0,37	1/2	380/415	50	1500	7,2	234,05	4"	310 113 001	*	234 761 1621L	1,5m	263,51		
234 762 1621	3P-0,55-380/415-50-W	W	3	0,55	3/4	380/415	50	1500	7,7	237,99	4"	310 113 001	*	234 762 1621L	1,5m	267,43	*	
234 763 1621	3P-0,75-380/415-50-W	W	3	0,75	1	380/415	50	1500	8,7	255,68	4"	310 113 001	*	234 763 1621L	1,5m	285,14	*	
234 724 1621	3P-1,1-380/415-50-W	W	3	1,1	1,5	380/415	50	3000	10,2	296,76	4"	310 113 001	*	234 724 1621L	1,5m	326,22	*	
234 725 1621	3P-1,5-380/415-50-W	W	3	1,5	2	380/415	50	3000	11,2	344,94	4"	310 113 001	*	234 725 1621L	1,5m	374,40	*	
234 726 2521	3P-2,2-380/415-50-W	W	3	2,2	3	380/415	50	4000	12,6	427,82	4"	310 113 001	*	234 726 2521L	2,5m	463,41	*	
234 764 2521	3P-3-380/415-50-W	W	3	3	4	380/415	50	4000	15	516,45	4"	310 113 001	*	234 764 2521L	2,5m	552,05	*	
4" SUPER STAINLESS - 3 PHASES, 316 SS (1 Lead Required)																		
234 761 0521	3P-0,37-380/415-50-S	S	3	0,37	1/2	380/415	50	1500	7,2	433,66	4"	310 113 501	*	234 761 0521L	1,5m	490,06		
234 762 0521	3P-0,55-380/415-50-S	S	3	0,55	3/4	380/415	50	1500	7,7	435,69	4"	310 113 501	*	234 762 0521L	1,5m	492,09		
234 763 0521	3P-0,75-380/415-50-S	S	3	0,75	1	380/415	50	1500	8,7	454,14	4"	310 113 501	*	234 763 0521L	1,5m	510,54		
234 724 0521	3P-1,1-380/415-50-S	S	3	1,1	1,5	380/415	50	3000	10,2	495,04	4"	310 113 501	*	234 724 0521L	1,5m	551,43		
234 725 0521	3P-1,5-380/415-50-S	S	3	1,5	2	380/415	50	3000	11,2	545,14	4"	310 113 501	*	234 725 0521L	1,5m	601,55		
234 726 2221	3P-2,2-380/415-50-S	S	3	2,2	3	380/415	50	4000	12,6	631,33	4"	310 113 501	*	234 726 2221L	2,5m	691,97		
234 764 2221	3P-3-380/415-50-S	S	3	3	4	380/415	50	4000	15	723,53	4"	310 113 501	*	234 764 2221L	2,5m	784,16		
5% adder to above prices for 500V-50Hz-3 phase version; no price adder on 230V-50Hz-3phase version																		
Leads																		
310 113 001	LEAD4 - 4x1.5; Length = 1.5m standard								0,3	22,53	Acc	*						
310 113 002	LEAD4 - 4x1.5; Length = 2.5m standard								0,4	28,70	Acc	*						
310 113 401	LEAD4 - 4x1.5; Length = 1.5m 304 SS								0,3	27,50	Acc	*						
310 113 402	LEAD4 - 4x1.5; Length = 2.5m 304 SS								0,4	33,68	Acc	*						
310 111 001	LEAD4 - 4x1.5; Length = 1.5m + plug								0,3	38,94	Acc	*						
310 111 002	LEAD4 - 4x1.5; Length = 2.5m + plug								0,4	43,04	Acc	*						
310 112 001	LEAD4 - 4x1.5/L=1.5m + plug + traction relief								0,3	43,04	Acc	*						
310 112 002	LEAD4 - 4x1.5/L=2.5m + plug + traction relief								0,4	47,15	Acc	*						
310 113 501	LEAD4 - 4x1.5/L=1.5m/ VDE 316 SS/V4A								0,3	49,60	Acc	*						
310 113 502	LEAD4 - 4x1.5;L=2.5m VDE 316SS/V4A								0,4	53,88	Acc	*						

W = Standard Material Version; S = Complete 316 SS Version



**Encapsulated Submersible Motors
4" 3 Phases 50 Hz 6500 N
Euro Price List**

3~ High Thrust Motors

PRICE LIST EFFECTIVE 01-MAY-2011 ORDER DATE All below motors do have a thrust load of 6500 N = High Thrust
All below listed 3 phases motors are direct on line

* Normally stocked. Call for Availability. Motors listed on this page do not include leads

**single packed
without lead**

**Motor & Cable &
Single Pack**

Model Number	DESCRIPTION	Material	Phases	kW	HP	Voltage	Hertz	Thrust (N)	Net Weight (kg)	Цена с НДС, Euro	Price Group	standard lead -not included-	STOCK STATUS*	MODEL	attached lead	Цена с НДС, Euro	STOCK STATUS*	
4" High Thrust - 3 Phase (1 Lead Req'd)																		
234 726 3421	3P-2,2-380/415-50-W	W	3	2,2	3	380/415	50	6500	16,8	602,32	4"	310 113 002	*	234 726 3421L	2,5m	630,87	*	
234 764 3421	3P-3-380/415-50-W	W	3	3	4	380/415	50	6500	18,9	628,07	4"	310 113 002	*	234 764 3421L	2,5m	656,63	*	
234 727 3421	3P-3,7-380/415-50-W	W	3	3,7	5	380/415	50	6500	20,9	657,78	4"	310 113 002	*	234 727 3421L	2,5m	686,33	*	
234 765 3421	3P-4-380/415-50-W	W	3	4	5.5	380/415	50	6500	21,8	713,25	4"	310 113 002	*	234 765 3421L	2,5m	741,81	*	
234 728 3421	3P-5,5-380/415-50-W	W	3	5,5	7.5	380/415	50	6500	28,7	832,13	4"	310 113 002	*	234 728 3421L	2,5m	860,70	*	
234 729 3421	3P-7,5-380/400/415-50-W	W	3	7,5	10	380/415	50	6500	32,7	1 085,93	4"	310 113 002	*	234 729 3421L	2,5m	1 114,49	*	
4" High Thrust - 3 Phase, 316SS/V4A (1 Lead Req'd)																		
234 726 3521	3P-2,2-380/415-50-S	S	3	2,2	3	380/415	50	6500	16,8	784,18	4"	310 113 502		234 726 3521L	2,5m	861,32		
234 764 3521	3P-3-380/415-50-S	S	3	3	4	380/415	50	6500	18,9	834,53	4"	310 113 502		234 764 3521L	2,5m	888,14		
234 727 3521	3P-3,7-380/415-50-S	S	3	3,7	5	380/415	50	6500	20,9	865,40	4"	310 113 502		234 727 3521L	2,5m	919,01		
234 765 3521	3P-4-380/415-50-S	S	3	4	5.5	380/415	50	6500	21,8	923,11	4"	310 113 502		234 765 3521L	2,5m	976,72		
234 728 3521	3P-5,5-380/415-50-S	S	3	5,5	7.5	380/415	50	6500	28,7	1 046,73	4"	310 113 502		234 728 3521L	2,5m	1 100,32		
234 729 3521	3P-7,5-380/400/415-50-S	S	3	7,5	10	380/415	50	6500	32,7	1 292,56	4"	310 113 502		234 729 3521L	2,5m	1 321,12		
5% adder to above prices for 500V-50Hz-3 phase version																		
Leads																		
310 113 002	LEAD4 - 4x1.5/L=2.5m standard								0,4	28,70	Acc	*						
310 113 402	LEAD4 - 4x1.5/L=2.5m 304 SS								0,4	33,68	Acc	*						
310 113 502	LEAD4 - 4x1.5;L=2.5m VDE 316SS/V4A								0,4	53,88	Acc	*						
W = Standard Material Version; S = Complete 316 SS Version																		

**Franklin Electric****Encapsulated Submersible Motors****4" 3 Phases 220/230V 50 Hz****3x220V Motors****Motor & Cable & Single Pack**

All below listed 3 phases motors are direct on line. Motors listed on this page do not include leads

PRICE LIST EFFECTIVE 01-MAY-2011 ORDER DATE

Model Number	DESCRIPTION	Material	Phases	kW	HP	Voltage	Hertz	Thrust (N)	Net Weight (kg)	Цена с НДС, Euro	Price Group	standard lead -not included-	STOCK STATUS*	MODEL	attached lead 304SS	Цена с НДС, Euro	STOCK STATUS*	
4" SUPER STAINLESS - 3 PHASES (1 Lead Required)													without lead					
234 751 1621	3P-0,37-220/230-50-W	W	3	0,37	1/2	220/230	50	1500	7,3	234,05	4"	310 113 001	*	234 751 1621L	1,5m	263,51		
234 752 1621	3P-0,55-220/230-50-W	W	3	0,55	3/4	220/230	50	1500	8,3	237,99	4"	310 113 001	*	234 752 1621L	1,5m	267,43		
234 753 1621	3P-0,75-220/230-50-W	W	3	0,75	1	220/230	50	1500	9,6	255,68	4"	310 113 001	*	234 753 1621L	1,5m	285,14		
234 754 1621	3P-1,1-220/230-50-W	W	3	1,1	1,5	220/230	50	3000	10,8	296,76	4"	310 113 001	*	234 754 1621L	1,5m	326,22		
234 755 1621	3P-1,5-220/230-50-W	W	3	1,5	2	220/230	50	3000	12,1	344,94	4"	310 113 001	*	234 755 1621L	1,5m	374,40		
234 756 2521	3P-2,2-220/230-50-W	W	3	2,2	3	220/230	50	4000	13,5	427,82	4"	310 113 001	*	234 756 2521L	2,5m	463,41		
234 766 2521	3P-3-220/230-50-W	W	3	3	4	220/230	50	4000	16,8	516,45	4"	310 113 001	*	234 766 2521L	2,5m	552,05		
4" SUPER STAINLESS - 3 PHASES, 316 SS (1 Lead Required)																		
234 751 0521	3P-0,37-220/230-50-S	S	3	0,37	1/2	220/230	50	1500	7,6	433,66	4"	310 113 501		234 751 0521L	1,5m	490,06		
234 752 0521	3P-0,55-220/230-50-S	S	3	0,55	3/4	220/230	50	1500	8,5	435,69	4"	310 113 501		234 752 0521L	1,5m	492,09		
234 753 0521	3P-0,75-220/230-50-S	S	3	0,75	1	220/230	50	1500	9,7	454,14	4"	310 113 501		234 753 0521L	1,5m	510,54		
234 754 0521	3P-1,1-220/230-50-S	S	3	1,1	1,5	220/230	50	3000	11,1	495,04	4"	310 113 501		234 754 0521L	1,5m	551,43		
234 755 0521	3P-1,5-220/230-50-S	S	3	1,5	2	220/230	50	3000	12,3	545,14	4"	310 113 501		234 755 0521L	1,5m	601,55		
234 756 2221	3P-2,2-220/230-50-S	S	3	2,2	3	220/230	50	4000	13,5	631,33	4"	310 113 501		234 756 2221L	2,5m	691,97		
234 766 2221	3P-3-220/230-50-S	S	3	3	4	220/230	50	4000	17,3	723,53	4"	310 113 501		234 766 2221L	2,5m	784,16		
4" High Thrust - 3 Phase (1 Lead Req'd)													without lead					
234 756 3421	3P-2,2-220/230-50-W	W	3	2,2	3	220/230	50	6500	16,1	602,32	4"	310 113 002		234 756 3421L	2,5m	630,87		
234 766 3421	3P-3-220/230-50-W	W	3	3	4	220/230	50	6500	19,1	628,07	4"	310 113 002		234 766 3421L	2,5m	656,63		
234 757 3421	3P-3,7-220/230-50-W	W	3	3,7	5	220/230	50	6500	20,9	657,78	4"	310 113 002		234 757 3421L	2,5m	686,33		
234 767 3421	3P-4-220/230-50-W	W	3	4	5,5	220/230	50	6500	24,1	713,25	4"	310 113 002		234 767 3421L	2,5m	741,81		
234 758 3421	3P-5,5-220/230-50-W	W	3	5,5	7,5	220/230	50	6500	29,4	832,13	4"	310 113 002		234 758 3421L	2,5m	860,70		
4" High Thrust - 3 Phase, 316SS/V4A (1 Lead Req'd)																		
234 756 3521	3P-2,2-220/230-50-S	S	3	2,2	3	220/230	50	6500	16,1	807,71	4"	310 113 502		234 756 3521L	2,5m	861,32		
234 766 3521	3P-3-220/230-50-S	S	3	3	4	220/230	50	6500	19,1	834,53	4"	310 113 502		234 766 3521L	2,5m	888,14		
234 757 3521	3P-3,7-220/230-50-S	S	3	3,7	5	220/230	50	6500	20,9	865,40	4"	310 113 502		234 757 3521L	2,5m	919,01		
234 767 3521	3P-4-220/230-50-S	S	3	4	5,5	220/230	50	6500	24,1	923,11	4"	310 113 502		234 767 3521L	2,5m	976,72		
234 758 3521	3P-5,5-220/230-50-S	S	3	5,5	7,5	220/230	50	6500	29,4	1 046,73	4"	310 113 502		234 758 3521L	2,5m	1 100,32		
Leads																		
310 113 001	LEAD4 - 4x1.5; Length = 1.5m standard								0,3	22,53	Acc	YES						
310 113 002	LEAD4 - 4x1.5; Length = 2.5m standard								0,4	28,70	Acc	YES						
310 113 401	LEAD4 - 4x1.5; Length = 1.5m 304 SS								0,3	27,50	Acc	YES						
310 113 402	LEAD4 - 4x1.5; Length = 2.5m 304 SS								0,4	33,68	Acc	YES						
310 111 001	LEAD4 - 4x1.5; Length = 1.5m + plug								0,3	38,94	Acc	YES						
310 111 002	LEAD4 - 4x1.5; Length = 2.5m + plug								0,4	43,04	Acc	YES						
310 112 001	LEAD4 - 4x1.5/L=1.5m + plug + traction relief								0,3	43,04	Acc	YES						
310 112 002	LEAD4 - 4x1.5/L=2.5m + plug + traction relief								0,4	47,15	Acc	YES						
310 113 501	LEAD4 - 4x1.5/L=1.5m/ VDE 316 SS/V4A								0,3	49,60	Acc	YES	W = Standard Material Version					
310 113 502	LEAD4 - 4x1.5/L=2.5m VDE 316SS/V4A								0,4	53,88	Acc	YES	S = Complete 316 SS Version					



Franklin Electric

PRICE LIST EFFECTIVE 01-MAY-2011 ORDER

SubTronic ControlBox

* = Normally stocked. Call for Availability. Non-stock - call for lead time.

MODEL	DESCRIPTION	Material	Phases	kW	HP	Voltage	Hertz	Thrust (N)	Gross Weight (kg)	Remarks	Цена с НДС, Euro	Price Group	STOCK STATUS*
284 623 3511	SUB-TR-0.25-230-50-PSC			0,3	1/3	230	50				125,24	Acc	
284 624 3511	SUB-TR-0.37-230-50-PSC			0,4	1/2	230	50				127,51	Acc	
284 625 3511	SUB-TR-0.55-230-50-PSC			0,6	3/4	230	50				129,79	Acc	
284 626 3511	SUB-TR-0.75-230-50-PSC			0,8	1	230	50				132,07	Acc	
284 627 3511	SUB-TR-1.1-230-50-PSC			1,1	1.5	230	50				145,73	Acc	
284 628 3511	SUB-TR-1.5-230-50-PSC			1,5	2	230	50				159,39	Acc	
284 629 3511	SUB-TR-2.2-230-50-PSC			2,2	3	230	50				166,22	Acc	



Franklin Electric

PRICE LIST EFFECTIVE 01-MAY-2011 ORDER

SubDrive, 60Hz motors

* = Normally stocked. Call for Availability. Non-stock - call for lead time.

MODEL	DESCRIPTION	Phases	kW	Hertz	Thrust (N)	Gross Weight (kg)	Remarks	Цена с НДС, Euro	STOCK STATUS*
5870203380	CP WATER SUB DRIVE 75							996,19	
5870204100	CP WATER SUB DRIVE 100							1 197,70	
5870204150	CP WATER SUB DRIVE 150							1 571,13	
5870206300	CP WATER SUB DRIVE 300							3 039,80	
2347141621L	3P-1.4-230-60-W-Lead		1,4	60				326,22	
2347151621L	3P-1.8-230-60-W-Lead		1,8	60				374,40	
2347162521L	3P-2.5-230-60-W-Lead		2,5	60				463,41	
2347173421L	3P-4.2-230-60-W-Lead		4,2	60				686,33	



Franklin Electric

SubMonitor ControlBox

PRICE LIST EFFECTIVE 01-MAY-2011 ORDER DATE

* *Normally* stocked. Call for Availability. Non-stock - call for lead time.

SUBMONITOR		kW		Цена с НДС, Euro		
586 000 5100	380, 400, 415 V, 50 Hz	<= 150		894,56	ACC	*



Franklin Electric

**Encapsulated Submersible Motors
6" 380/415 V 50 Hz Sandfighter**

6" Encapsulated Motors

SS 304

**Sandfighter Execution and 4m Lead(s) assembled
Endbells in Cast Iron; Stator Shell in 304 SS; SIC Seal**

All motors listed below are 3 phases

Motors listed on this page do include leads

PRICE LIST EFFECTIVE 01-MAY-2011 ORDER DATE Euro Price List

MODEL	DESCRIPTION	Material	Phases	kW	HP	Voltage	Hertz	Thrust (N)	Net Weight (kg)	Remarks	Цена с НДС, Euro	Price Group	Motor Cable	STOCK STATUS*	
Direct On Line Start															
236 610 9061	3P-4-380/415-50-SIC-W-LEAD	W	3	4	5,5	380/415	50	15500	37,5	SIC	1 229,06	6"	310 125 004	*	
236 611 9061	3P-5,5-380/415-50-SIC-W-LEAD	W	3	5,5	7,5	380/415	50	15500	41,1	SIC	1 269,99	6"	310 125 004	*	
236 612 9061	3P-7,5-380/415-50-SIC-W-LEAD	W	3	7,5	10	380/415	50	15500	45,2	SIC	1 338,23	6"	310 125 004	*	
236 001 9061	3P-9,3-380/415-50-SIC-W-LEAD	W	3	9,3	12,5	380/415	50	15500	47,5	SIC	1 433,78	6"	310 125 004	*	
236 613 9061	3P-11-380/415-50-SIC-W-LEAD	W	3	11	15	380/415	50	15500	50,9	SIC	1 505,93	6"	310 125 004	*	
236 614 9061	3P-15-380/415-50-SIC-W-LEAD	W	3	15	20	380/415	50	15500	56,7	SIC	1 759,43	6"	310 125 004	*	
236 615 9061	3P-18,5-380/415-50-SIC-W-LEAD	W	3	18,5	25	380/415	50	15500	63,3	SIC	1 910,46	6"	310 125 004	*	
236 616 9061	3P-22-380/415-50-SIC-W-LEAD	W	3	22	30	380/415	50	15500	69,3	SIC	2 147,33	6"	310 125 004	*	
236 617 9061	3P-30-380/415-50-SIC-W-LEAD	W	3	30	40	380/415	50	27500	83,9	SIC	2 792,52	6"	310 145 004	*	
276 618 6061	3P-37-380/415-50-W-SIC-SB-LEAD	W	3	37	50	380/415	50	27500	136	SB, SIC	3 902,42	6"	310 145 004	*	
276 619 6061	3P-45-380/415-50-W-SIC-SB-LEAD	W	3	45	60	380/415	50	27500	150	SB, SIC	4 654,16	6"	310 145 004	*	
ADDER XXL-BEARING															
Star Delta Start															
236 710 9061	3P-4-380/415-50-SIC-SD-LEAD	W	3	4	5,5	380/415	50	15500	37,5	SIC	1 325,20	6"	310 125 004	*	
236 711 9061	3P-5,5-380/415-50-SIC-SD-LEAD	W	3	5,5	7,5	380/415	50	15500	41,1	SIC	1 366,15	6"	310 125 004	*	
236 712 9061	3P-7,5-380/415-50-SIC-SD-LEAD	W	3	7,5	10	380/415	50	15500	45,2	SIC	1 434,38	6"	310 125 004	*	
236 011 9061	3P-9,3-380/415-50-SIC-SD-LEAD	W	3	9,3	12,5	380/415	50	15500	47,5	SIC	1 529,94	6"	310 125 004	*	
236 713 9061	3P-11-380/415-50-SIC-SD-LEAD	W	3	11	15	380/415	50	15500	50,9	SIC	1 602,07	6"	310 125 004	*	
236 714 9061	3P-15-380/415-50-SIC-SD-LEAD	W	3	15	20	380/415	50	15500	56,7	SIC	1 855,56	6"	310 125 004	*	
236 715 9061	3P-18,5-380/415-50-SIC-SD-LEAD	W	3	18,5	25	380/415	50	15500	63,3	SIC	2 006,60	6"	310 125 004	*	
236 716 9061	3P-22-380/415-50-SIC-SD-LEAD	W	3	22	30	380/415	50	15500	69,3	SIC	2 243,48	6"	310 125 004	*	
236 717 9061	3P-30-380/415-50-SIC-SD-LEAD	W	3	30	40	380/415	50	27500	83,9	SIC	2 853,14	6"	310 125 004	*	
276 718 6061	3P-37-380/415-50-W-SIC-SB-LEAD	W	3	37	50	380/415	50	27500	136	SB, SIC	3 963,98	6"	310 125 004	*	
276 719 6061	3P-45-380/415-50-W-SIC-SB-LEAD	W	3	45	60	380/415	50	27500	150	SB, SIC	4 787,85	6"	310 145 004	*	
Price Adder for XXL Bearing		last digit of model numberchanges to "3"				NEW		45000		4 - 30kW		341,28	6"		
PUMP FIXTURE															
275 334 304	Screw 38,1 mm										3,58	Acc		*	
275 547 113	Lockwasher										0,45	ACC		*	
308 659 316	Pump Fixture Kit 38,1 mm										21,24	ACC		*	



Franklin Electric

**Encapsulated Submersible Motors
6" 380/415 50 Hz 316 SS**

Euro Price List

All motors listed below are 3 phases

Sandfighter Execution and 4m Lead(s) assembled

Motors in complete 316 Stainless Steel and with SIC Seal

PRICE LIST EFFECTIVE 01-MAY-2011 ORDER DATE

6" Encapsulated Motors

SS 316

MODEL	DESCRIPTION	Material	Phases	kW	HP	Voltage	Hertz	Thrust (N)	Net Weight (kg)	Remarks	Цена с НДС, Euro	Price Group	standard lead	STOCK STATUS*
Direct On Line Start														
236 610 3961	3P-4-380/415-50-S	S	3	4	5.5	380/415	50	15500	36,8		2 174,32	6"	310 125 504	
236 611 3961	3P-5,5-380/415-50-S	S	3	5,5	7.5	380/415	50	15500	40,4		2 218,96	6"	310 125 504	*
236 612 3961	3P-7,5-380/415-50-S	S	3	7,5	10	380/415	50	15500	44,5		2 287,86	6"	310 125 504	*
236 001 3961	3P-9,3-380/415-50-S	S	3	9,3	12.5	380/415	50	15500	46,8		2 391,31	6"	310 125 504	
236 613 3961	3P-11-380/415-50-S	S	3	11	15	380/415	50	15500	50,2		2 466,35	6"	310 125 504	*
236 614 3961	3P-15-380/415-50-S	S	3	15	20	380/415	50	15500	56		2 734,04	6"	310 125 504	*
236 615 3961	3P-18,5-380/415-50-S	S	3	18,5	25	380/415	50	15500	62,6		2 843,26	6"	310 125 504	*
236 616 3961	3P-22-380/415-50-S	S	3	22	30	380/415	50	15500	68,6		3 093,44	6"	310 125 504	*
236 617 3961	3P-30-380/415-50-S	S	3	30	40	380/415	50	27500	83,2		3 783,38	6"	310 145 504	*
276 618 4061	3P-37-380/415-50-S-SB	S	3	37	50	380/415	50	27500	136	SB	6 102,68	6"	310 145 504	*
276 619 4061	3P-45-380/415-50-S-SB	S	3	45	60	380/415	50	27500	150	SB	6 884,47	6"	310 145 504	*
Star Delta Start														
236 710 3961	3P-4-380/415-50-S-SD	S	3	4	5.5	380/415	50	15500	36,8		2 324,76	6"	310 125 504	
236 711 3961	3P-5,5-380/415-50-S-SD	S	3	5,5	7.5	380/415	50	15500	40,4		2 369,41	6"	310 125 504	
236 712 3961	3P-7,5-380/415-50-S-SD	S	3	7,5	10	380/415	50	15500	44,5		2 438,32	6"	310 125 504	
236 011 3961	3P-9,3-380/415-50-S-SD	S	3	9,3	12.5	380/415	50	15500	46,8		2 541,77	6"	310 125 504	
236 713 3961	3P-11-380/415-50-S-SD	S	3	11	15	380/415	50	15500	50,2		2 616,83	6"	310 125 504	
236 714 3961	3P-15-380/415-50-S-SD	S	3	15	20	380/415	50	15500	56		2 884,51	6"	310 125 504	*
236 715 3961	3P-18,5-380/415-50-S-SD	S	3	18,5	25	380/415	50	15500	62,6		2 993,72	6"	310 125 504	
236 716 3961	3P-22-380/415-50-S-SD	S	3	22	30	380/415	50	15500	68,6		3 243,90	6"	310 125 504	
236 717 3961	3P-30-380/415-50-S-SD	S	3	30	40	380/415	50	27500	83,2		3 883,70	6"	310 125 504	
276 718 4061	3P-37-380/415-50-S-SD	S	3	37	50	380/415	50	27500	136	SB	6 204,54	6"	310 125 504	
276 719 4061	3P-45-380/415-50-S-SD	S	3	45	60	380/415	50	27500	150	SB	7 088,18	6"	310 145 504	
PUMP FIXTURE														
275 334 304	Screw 38,1 mm										3,58	Acc		*
275 547 113	Lockwasher										0,45	ACC		*
308 659 316	Pump Fixture Kit 38,1 mm										21,24	ACC		*



Franklin Electric

**Rewindable Submersible Motors
6" 380/415 V 50 Hz**

6" REW Motors

STANDARD EXECUTION + PVC WINDING

All motors listed below are 3 phases and include 4m lead(s)

Retrofitable PT100 kit (see price page "Accessories") can be used with any motor on this page.

PRICE LIST EFFECTIVE 01-MAY-2011 ORDER DATE Euro Price List

PE2/PA Windings

MODEL	DESCRIPTION	Material	Phases	kW	HP	Voltage	Hertz	Thrust (N)	Net Weight (kg)	Remarks	Цена с НДС, Euro	Price Group	STOCK STATUS*	Model	Цена с НДС, Euro	Price Group	STOCK STATUS*
Direct On Line Start																	
262 610 5011	6RW-4-380/415-50-W	W	3	4	5.5	380/415	50	15500	48		1 442,07	6"		262 610 5211	1 874,69	6"	
262 611 5011	6RW-5,5-380/415-50-W	W	3	5,5	7.5	380/415	50	15500	48		1 442,07	6"	*	262 611 5211	1 874,69	6"	
262 612 5011	6RW-7,5-380/415-50-W	W	3	7,5	10	380/415	50	15500	50		1 510,27	6"	*	262 612 5211	1 963,35	6"	
262 231 5011	6RW-9,3-380/415-50-W	W	3	9,3	12.5	380/415	50	15500	53		1 543,51	6"	*	262 231 5211	2 006,57	6"	
262 613 5011	6RW-11-380/415-50-W	W	3	11	15	380/415	50	15500	56		1 601,59	6"	*	262 613 5211	2 082,07	6"	
262 232 5011	6RW-13-380/415-50-W	W	3	13	17,5	380/415	50	15500	61		1 724,47	6"	*	262 232 5211	2 241,82	6"	
262 614 5011	6RW-15-380/415-50-W	W	3	15	20	380/415	50	15500	66		1 903,58	6"	*	262 614 5211	2 474,66	6"	
262 615 5011	6RW-18,5-380/415-50-W	W	3	18,5	25	380/415	50	15500	70		2 146,44	6"	*	262 615 5211	2 790,37	6"	
262 616 5011	6RW-22-380/415-50-W	W	3	22	30	380/415	50	15500	79		2 391,08	6"	*	262 616 5211	3 108,40	6"	
262 233 5011	6RW-26-380/415-50-W	W	3	26	35	380/415	50	15500	90		2 603,24	6"	*	262 233 5211	3 384,22	6"	
262 617 5111	6RW-30-380/415-50-W	W	3	30	40	380/415	50	27500	100		2 828,77	6"	*	262 617 5311	3 677,41	6"	
262 618 5111	6RW-37-380/415-50-W	W	3	37	50	380/415	50	27500	107	PE2/PA	3 810,76	6"	*	Standard			
Star Delta Start																	
262 710 5011	6RW-4-380/415-50-W-SD	W	3	4	5.5	380/415	50	15500	48		1 534,39	6"		Not available			
262 711 5011	6RW-5,5-380/415-50-W-SD	W	3	5,5	7.5	380/415	50	15500	48		1 534,39	6"	*	Not available			
262 712 5011	6RW-7,5-380/415-50-W-SD	W	3	7,5	10	380/415	50	15500	50		1 602,63	6"	*	Not available			
262 331 5011	6RW-9,3-380/415-50-W-SD	W	3	9,3	12.5	380/415	50	15500	53		1 633,89	6"	*	Not available			
262 713 5011	6RW-11-380/415-50-W-SD	W	3	11	15	380/415	50	15500	56		1 691,36	6"	*	Not available			
262 332 5011	6RW-13-380/415-50-W-SD	W	3	13	17,5	380/415	50	15500	61		1 814,24	6"	*	Not available			
262 714 5011	6RW-15-380/415-50-W-SD	W	3	15	20	380/415	50	15500	66		1 993,42	6"	*	262 714 5211	2 591,46	6"	
262 715 5011	6RW-18,5-380/415-50-W-SD	W	3	18,5	25	380/415	50	15500	70		2 236,27	6"	*	262 715 5211	2 907,15	6"	
262 716 5011	6RW-22-380/415-50-W-SD	W	3	22	30	380/415	50	15500	79		2 480,92	6"	*	262 716 5211	3 225,19	6"	
262 333 5011	6RW-26-380/415-50-W-SD	W	3	26	35	380/415	50	15500	90		2 693,06	6"	*	262 333 5211	3 500,99	6"	
262 717 5111	6RW-30-380/415-50-W-SD	W	3	30	40	380/415	50	27500	100		2 916,71	6"	*	262 717 5311	3 791,71	6"	
262 718 5111	6RW-37-380/415-50-W-SD	W	3	37	50	380/415	50	27500	107	PE2/PA	3 899,13	6"	*	Standard			
5% adder to above prices for 500V-50Hz-3 phase versions																	



Franklin Electric

**Encapsulated Submersible Motors
8" 380 V 50 Hz**

Euro Price List

STANDARD EXECUTION

All motors listed below are 3 phases
Motors listed on this page including leads

8" Encapsulated Motors

SS 304

PRICE LIST EFFECTIVE 01-MAY-2011 ORDER DATE

MODEL	DESCRIPTION	Material	Phases	kW	HP	Voltage	Hertz	Thrust (N)	Net Weight (kg)	Remarks	Цена с НДС, Euro	Price Group	STOCK STATUS*	
Direct On Line Start														
239 600 7023	3P-30-380/415-50-W	W	3	30	40	380/415	50	45000	145	SB	4 663,69	8"	*	
239 601 7023	3P-37-380/415-50-W	W	3	37	50	380/415	50	45000	157	SB	5 012,57	8"	*	
239 602 7023	3P-45-380/415-50-W	W	3	45	60	380/415	50	45000	172	SB	5 419,59	8"	*	
239 603 7023	3P-55-380/415-50-W	W	3	55	75	380/415	50	45000	202	SB	6 139,40	8"	*	
239 604 7023	3P-75-380/415-50-W	W	3	75	100	380/415	50	45000	240	SB	7 719,36	8"	*	
239 105 7019	3P-93-380/415-50-W	W	3	93	125	380/415	50	45000	318	SB	10 191,40	8"	*	
239 106 7519	3P-110-380/415-50-W	W	3	110	150	380/415	50	45000	381	SB + SIC	12 323,69	8"	*	
239 107 7519	3P-130-380/415-50-W	W	3	130	175	380/415	50	45000	420	SB + SIC	13 797,39	8"	*	
239 108 7519	3P-150-380/415-50-W	W	3	150	200	380/415	50	45000	494	SB + SIC	17 085,64	8"	*	
Star Delta Start														
239 620 8023	3P-30-380/415-50-W-SD	W	3	30	40	380/415	50	45000	145	SB	5 076,73	8"	*	
239 621 8023	3P-37-380/415-50-W-SD	W	3	37	50	380/415	50	45000	157	SB	5 425,60	8"	*	
239 622 8023	3P-45-380/415-50-W-SD	W	3	45	60	380/415	50	45000	172	SB	5 832,64	8"	*	
239 623 8023	3P-55-380/415-50-W-SD	W	3	55	75	380/415	50	45000	202	SB	6 680,77	8"	*	
239 624 8023	3P-75-380/415-50-W-SD	W	3	75	100	380/415	50	45000	240	SB	8 260,73	8"	*	
239 125 8019	3P-93-380/415-50-W-SD	W	3	93	125	380/415	50	45000	318	SB	10 732,95	8"	*	
239 126 7619	3P-110-380/415-50-W-SD	W	3	110	150	380/415	50	45000	381	SB + SIC	12 965,29	8"	*	
239 127 7619	3P-130-380/415-50-W-SD	W	3	130	175	380/415	50	45000	420	SB + SIC	14 439,01	8"	*	
239 128 7619	3P-150-380/415-50-W-SD	W	3	150	200	380/415	50	45000	494	SB + SIC	17 727,24	8"	*	
8" - Leads														
305 243 901	LEAD8-3x8.4mm ² 8m-VDE/KTW, no ground, brass; 30 - 45 kW									3,4		428,74	Acc	*
305 310 901	LEAD8-3x16mm ² -8m-VDE/KTW, no ground, brass [55 -93 kW DOL; 55 - 150 kW SD]									6,1		708,92	Acc	*
305 309 901	LEAD8-3x35mm ² 8m-VDE/KTW, no ground, 316 SS [110 - 150 kW DOL]									11,0		981,88	Acc	*
308 051 080	Ground wire 30 – 45 kW									1,0		72,50	Acc	
308 053 080	Ground wire 55 – 150 kW									2,0		126,92	Acc	*
Adder for Sand Fighter SiC option											183,21	8"		



Franklin Electric

**Encapsulated Submersible Motors
8" 380 V 50 Hz 316 SS**

Euro Price List

All motors listed below are 3 phases
Motors listed on this page including leads
Motors in complete 316 Stainless Steel :

8" Encapsulated Motors

SS 316

PRICE LIST EFFECTIVE 01-MAY-2011 ORDER DATE

MODEL	DESCRIPTION	Material	Phases	kW	HP	Voltage	Hertz	Thrust (N)	Net Weight (kg)	Remarks	Цена с НДС, Euro	Price Group	STOCK STATUS*	
Direct On Line Start														
239 600 7223	3P-30-380/415-50-S	S	3	30	40	380/415	50	45000	145	SB	8 816,12	8"	*	
239 601 7223	3P-37-380/415-50-S	S	3	37	50	380/415	50	45000	157	SB	9 273,29	8"	*	
239 602 7223	3P-45-380/415-50-S	S	3	45	60	380/415	50	45000	172	SB	9 616,13	8"	*	
239 603 7223	3P-55-380/415-50-S	S	3	55	75	380/415	50	45000	202	SB	10 291,82	8"	*	
239 604 7223	3P-75-380/415-50-S	S	3	75	100	380/415	50	45000	240	SB	12 491,36	8"	*	
239 105 7219	3P-93-380/415-50-S	S	3	93	125	380/415	50	45000	318	SB	14 837,22	8"	*	
239 106 7219	3P-110-380/415-50-S	S	3	110	150	380/415	50	45000	381	SB	16 511,44	8"	*	
239 107 7219	3P-130-380/415-50-S	S	3	130	175	380/415	50	45000	420	SB	17 985,12	8"	*	
239 108 7219	3P-150-380/415-50-S	S	3	150	200	380/415	50	45000	494	SB	21 273,37	8"	*	
Star Delta Start														
239 620 8223	3P-30-380/415-50-S-SD	S	3	30	40	380/415	50	45000	145	SB	9 527,88	8"	*	
239 621 8223	3P-37-380/415-50-S-SD	S	3	37	50	380/415	50	45000	157	SB	9 985,05	8"	*	
239 622 8223	3P-45-380/415-50-S-SD	S	3	45	60	380/415	50	45000	172	SB	10 327,90	8"	*	
239 623 8223	3P-55-380/415-50-S-SD	S	3	55	75	380/415	50	45000	202	SB	11 003,62	8"	*	
239 624 8223	3P-75-380/415-50-S-SD	S	3	75	100	380/415	50	45000	240	SB	13 203,14	8"	*	
239 125 8219	3P-93-380/415-50-S-SD	S	3	93	125	380/415	50	45000	318	SB	15 549,02	8"	*	
239 126 8219	3P-110-380/415-50-S-SD	S	3	110	150	380/415	50	45000	381	SB	17 323,46	8"	*	
239 127 8219	3P-130-380/415-50-S-SD	S	3	130	175	380/415	50	45000	420	SB	18 797,17	8"	*	
239 128 8219	3P-150-380/415-50-S-SD	S	3	150	200	380/415	50	45000	494	SB	22 085,43	8"	*	
8" - Leads														
305 243 902	LEAD8-3x8.4mm ² 8m-VDE/KTW, no ground, 316 SS; 30 - 45 kW									3,4		605,62	Acc	*
305 310 951	LEAD8-3x16mm ² -8m-VDE/KTW, no ground, 316 SS [55 -93 kW DOL; 55 - 150 kW SD]									6,1		721,04	Acc	*
305 309 901	LEAD8-3x35mm ² 8m-VDE/KTW, no ground, 316 SS [110 - 150 kW DOL]									11,0		981,88	Acc	*
308 051 080	Ground wire 30 – 45 kW									1,0		72,50	Acc	*
308 053 080	Ground wire 55 – 150 kW									2,0		126,92	Acc	*



Rewindable Submersible Motors 8" 380/415 V 50 Hz

8" REW Motors

Euro Price List STANDARD EXECUTION

All motors listed below are 3 phases, include 6m lead(s) and SiC seal.
PT100 kit (see price page "Accessoires") can be added to any motor on this page.

PRICE LIST EFFECTIVE 01-MAY-2011 ORDER DATE

PE2/PA Windings

MODEL	DESCRIPTION	Material	Phases	kW	HP	Voltage	Hertz	Thrust (N)	Net Weight (kg)	Remarks	Цена с НДС, Euro	Price Group	STOCK STATUS*	MODEL	Цена с НДС, Euro	Price Group	STOCK STATUS*
Direct on Line Start																	
263 610 5111	8RW-30-380,415/460-50/60-W	W	3	30	40	380/415	50	45000	140		4 137,40	8"	*	263 610 5311	4 758,01	8"	
263 611 5111	8RW-37-380,415/460-50/60-W	W	3	37	50	380/415	50	45000	140		4 544,10	8"	*	263 611 5311	5 225,73	8"	
263 612 5111	8RW-45-380,415/460-50/60-W	W	3	45	60	380/415	50	45000	156		4 845,97	8"	*	263 612 5311	5 572,86	8"	
263 260 5111	8RW-52-380,415/460-50/60-W	W	3	52	70	380/415	50	45000	179		5 351,70	8"	*	263 260 5311	6 154,45	8"	
263 613 5111	8RW-55-380,415/460-50/60-W	W	3	55	75	380/415	50	45000	179		5 446,54	8"	*	263 613 5311	6 263,51	8"	
263 261 5111	8RW-60-380,415/460-50/60-W	W	3	60	80	380/415	50	45000	198		5 760,26	8"	*	263 261 5311	6 624,31	8"	
263 262 5111	8RW-67-380,415/460-50/60-W	W	3	67	90	380/415	50	45000	198		6 398,88	8"	*	263 262 5311	7 358,69	8"	
263 614 5111	8RW-75-380,415/460-50/60-W	W	3	75	100	380/415	50	45000	215		6 522,52	8"	*	263 614 5311	7 500,90	8"	
263 263 5111	8RW-83-380,415/460-50/60-W	W	3	83	111	380/415	50	45000	247		7 095,43	8"		263 263 5311	8 159,72	8"	
263 615 5111	8RW-93-380,415/460-50/60-W	W	3	93	125	380/415	50	45000	247		7 705,68	8"	*	263 615 5311	8 861,52	8"	
Star- Delta Start																	
263 710 5111	8RW-30-380,415/460-50/60-W-SD	W	3	30	40	380/415	50	45000	140		4 496,34	8"	*	263 710 5311	5 170,78	8"	
263 711 5111	8RW-37-380,415/460-50/60-W-SD	W	3	37	50	380/415	50	45000	140		4 903,00	8"	*	263 711 5311	5 638,45	8"	
263 712 5111	8RW-45-380,415/460-50/60-W-SD	W	3	45	60	380/415	50	45000	156		5 204,88	8"	*	263 712 5311	5 985,61	8"	
263 270 5111	8RW-52-380,415/460-50/60-W-SD	W	3	52	70	380/415	50	45000	179		5 717,57	8"	*	263 270 5311	6 575,21	8"	
263 713 5111	8RW-55-380,415/460-50/60-W-SD	W	3	55	75	380/415	50	45000	179		5 916,92	8"	*	263 713 5311	6 804,48	8"	
263 271 5111	8RW-60-380,415/460-50/60-W-SD	W	3	60	80	380/415	50	45000	198		6 108,72	8"	*	263 271 5311	7 025,01	8"	
263 272 5111	8RW-67-380,415/460-50/60-W-SD	W	3	67	90	380/415	50	45000	198		6 712,50	8"	*	263 272 5311	7 719,36	8"	
263 714 5111	8RW-75-380,415/460-50/60-W-SD	W	3	75	100	380/415	50	45000	215		6 992,95	8"	*	263 714 5311	8 041,89	8"	
263 273 5111	8RW-83-380,415/460-50/60-W-SD	W	3	83	111	380/415	50	45000	247		7 518,80	8"	*	263 273 5311	8 646,62	8"	
263 715 5111	8RW-93-380,415/460-50/60-W-SD	W	3	93	125	380/415	50	45000	247		8 176,10	8"	*	263 715 5311	9 402,51	8"	
For additional cable sizes or lengths, or customer supplied cables please contact customer service																	
5% adder to above prices for 500V-50Hz-3 phase version																	